



HTM SNOWMAKING WATER HYDRANTS

The **HTM H-Series and E-Series** Snowmaking Hydrants are self-draining hydrants designed specifically for snowmaking. Their unique valve design offers precise water pressure control. The valve will not vibrate open under flow conditions!

- All valve components are made of bronze and stainless steel for long life
- Available in 10 standard riser lengths from 30 cm (1 foot) to 300 cm (9.8 feet)
- Custom riser lengths are also available up to 400 cm (13.1 feet)
- Available with 90° outlet (standard) or 45° outlet (optional)
- Galvanized steel shaft extension and riser pipe
- Stainless steel operating shaft and solid stainless steel shaft pins
- Leak-proof graphite foil shaft seal packing
- Aluminum operating handle
- Removable valve assembly permits complete servicing through the top of the hydrant—exclusive to HTM
- Use with HTM's 750 PSI rated 1½, 2, or 2½ inch camlock hose adapters

BEST LONG TERM INVESTMENT ON THE MARKET



H-Series

H-Series Hydrant

- Best for deep buried installations
- Internally mounted drain valves
- 2000 PSI inlet pressure rating
- 1200 PSI discharge pressure rating
- 2" or 2½" inch size
- Male or Female inlet
- NPT or BSPT threads

E-Series Hydrant

- Best for surface installations
- Externally mounted drain valve
- 1500 PSI inlet pressure rating
- 1200 PSI discharge pressure rating
- 2" size only
- Male inlet
- NPT or BSPT threads



E-Series

Victaulic® style inlet is also available